

Monitor / Controller / Access Control System

Monitor				
LED Monitors				
<div>SMT-4031</div> <div></div> <div>40"LED Monitor<ul style="list-style-type: none"><li>Support up to 1,920 x 1,080 resolution</li><li>Fast response time 8ms</li><li>High contrast ratio 5,000 : 1</li><li>Video Input : HDMI/VGA/Component (CVBS common)</li><li>Excellent picture quality with LED back light</li></ul></div>	<div>SMT-3231</div> <div></div> <div>32"LED Monitor<ul style="list-style-type: none"><li>Support up to 1,920 x 1,080 resolution</li><li>Fast response time 8ms</li><li>High contrast ratio 5,000 : 1</li><li>Video Input : HDMI/VGA/Component (CVBS common)</li><li>Excellent picture quality with LED back light</li></ul></div>	<div>SMT-2730/2232</div> <div></div> <div>27" LED / 21.5" Wide LED Monitor<ul style="list-style-type: none"><li>Support up to 1,920 x 1,080 resolution</li><li>Fast response time 8ms (SMT-2730) 5ms (SMT-2232)</li><li>High Contrast ratio 1,000 : 1</li><li>Video Input : HDMI, VGA, Composite</li><li>120Hz motion technology (SMT-2232)</li></ul></div>	<div>SMT-1930/1934</div> <div></div> <div>18.5" Wide LED / 19" LED Monitor<ul style="list-style-type: none"><li>Support up to 1,360 x 768 resolution (SMT-1930)</li><li>Support up to 1,280 x 1,024 resolution (SMT-1934)</li><li>Fast response time 5ms</li><li>High contrast ratio 1,000 : 1</li><li>Video Input : HDMI, VGA, Composite</li><li>120Hz motion technology (SMT-1930)</li></ul></div>	<div>SMT-1914/1734</div> <div></div> <div>19" LED / 17" LED Monitor<ul style="list-style-type: none"><li>Support up to 1,280 x 1,024 resolution</li><li>Fast response time 5ms</li><li>High contrast ratio 1,000 : 1</li><li>Video Input : VGA (SMT-1914) HDMI, VGA, BNC (SMT-1734)</li><li>Tempered glass screen</li></ul></div>
Controller				
<div>SPC-6000</div> <div></div> <div>System Control Keyboard<ul style="list-style-type: none"><li>5" TFT touch LCD</li><li>Control PTZ dome cameras, DVRs and matrix switchers</li><li>Up to 255 units with a single controller</li><li>Connect to a system up to 16 controllers</li></ul></div>	<div>SPC-2010</div> <div></div> <div>PTZ / DVR System Controller<ul style="list-style-type: none"><li>Control up to 255 PTZ cameras/DVRs</li><li>Built-in 3 axis twist zoom joystick</li><li>Built-in Jog shuttle</li><li>16 x 2 Character LCD display</li><li>RS-485 and RS-422 interface</li></ul></div>	<div>SPC-1010</div> <div></div> <div>PTZ Control Keyboard<ul style="list-style-type: none"><li>Control up to 255 PTZ cameras</li><li>Multi protocols supports</li><li>OSD Menu, 3D joystick control</li><li>RS-485 and RS-422 interface</li></ul></div>	<div>SPC-300</div> <div></div> <div>Coaxial Remote Controller<ul style="list-style-type: none"><li>Control via coaxial cable or RS-485</li><li>Camera connected : 1 unit</li><li>Cable extension : max. 500m (with 5C-2V cable)</li><li>RS-485 and RS-232C interface</li></ul></div>	<div>SPC-200</div> <div></div> <div>Camera Zoom &amp; OSD Controller<ul style="list-style-type: none"><li>Camera zoom in/out, OSD control</li><li>RS-485 communication</li><li>Zoom camera RJ-45 connector control</li></ul></div>
Access Control System				
Readers				
<div>SSA-R2010/R2011</div> <div></div> <div>Proximity / Smart Card, Fingerprint Reader<ul style="list-style-type: none"><li>125KHz Proximity/13.56MHz Contact-less Smart Card and Fingerprint Recognition</li><li>1 : 1 Verification and 1 : N Identification storable 2 Fingerprint Templates</li><li>1,000 Fingerprint Users and 10,000 ID Users</li><li>Auto Touch sensor for fingerprint only identification</li></ul></div>	<div>SSA-R2000/R2001</div> <div></div> <div>Proximity / Smart Card &amp; PIN Reader<ul style="list-style-type: none"><li>125KHz Proximity / 13.56MHz (MIFARE) Contact-less Smart Card / PIN Reader</li><li>12 Numeric Keypads with Back Lighting</li><li>External LED control</li><li>External buzzer control</li><li>Tamper Switch</li></ul></div>	<div>SSA-R1000/R1001/ R1100/R1101</div> <div></div> <div>Proximity / Smart Card / EM Reader<ul style="list-style-type: none"><li>125KHz proximity / 13.56MHz contact-less smart card / Reader</li><li>26/34bit wiegand output format</li><li>External LED control</li><li>External buzzer control</li><li>Indoor / outdoor operation</li></ul></div>	<div>SSA-PE1202</div> <div></div> <div>Lift Access Control Panel<ul style="list-style-type: none"><li>Controls up to 384 floors (12floors per control panel, expandable up to 32 control panel)</li><li>Up to 50,000 users and 20,000 event buffers</li><li>26/34 bit wiegand switchable</li><li>Integration with SSA-P4xx series control panel</li><li>Real-time monitoring of lift access and alarm status</li></ul></div>	<div>SSA-P420T/P421T/ 400T/401T</div> <div></div> <div>Intelligent 4 Doors Access Controller<ul style="list-style-type: none"><li>Up to 50,000 Users and 29,500 Event Buffers</li><li>Standalone/Network communication via RS-232/RS-422/RS-485, TCP/IP</li><li>Independent 15 inputs and 15 outputs including 12ea of 2 Form-C Relay outputs</li><li>Power Package (SSA-P420T/421T)</li></ul></div>
Control Panel				
Card				
<div>SSA-P112T/P102T</div> <div></div> <div>Intelligent Single Door Access Controller<ul style="list-style-type: none"><li>Up to 50,000 Users and 50,000 Event Buffers</li><li>Standalone / Network Communication via RS-232/RS-422/RS-485 (SSA-P112T)</li><li>Independent 5 inputs and 4 Outputs including 2ea of 2 Form-C Relay Outputs</li><li>Power Package (SSA-P112T)</li></ul></div>	<div>SSA-X100</div> <div></div> <div>Power Package for Control Panel<ul style="list-style-type: none"><li>Power package for control panel</li><li>Communication status via LED indicator</li><li>Surge protection (NFB)</li><li>Low battery check</li><li>AC power failure check</li><li>Battery recharge circuit</li></ul></div>	<div>SSA-C100/C200/C110</div> <div></div> <div>Proximity Card<ul style="list-style-type: none"><li>125KHz / passive type (SSA-C100/C110)</li><li>13.56MHz / passive type (SSA-C200)</li><li>ISO credit card size and thickness (SSA-C100/C200)</li><li>Clamshell type (SSA-C110)</li></ul></div>	<div>SSA-X500</div> <div></div> <div>Finger Print Scanner<ul style="list-style-type: none"><li>Compact and elegant design, which is more convenient to use</li><li>Excellent product durability that assures a long life</li><li>Provides USB interface</li></ul></div>	<div>SSA-M2000/M2100</div> <div></div> <div>SAMS (Samsung Access Management Software) Pro / Pro Lite<ul style="list-style-type: none"><li>Video surveillance integration allowing control of cameras and digital video recorders</li><li>Supports multiple sites</li><li>Supports multiple languages</li><li>Dynamic card holder and ID management function</li><li>Graphical map for ease of navigation</li></ul></div>

The Eco mark represents Samsung Techwin's will to create environment-friendly products, and indicates that the product satisfies the EU RoHS Directive.

DISTRIBUTED BY

SAMSUNG TECHWIN CO., LTD. 701, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do Korea 463-400  
Tel : +82-70-7147-8741~8749, 8752~8760 Fax : +82-31-8018-3745 www.samsungsecurity.com www.samsungcctv.com  
COPYRIGHT BY SAMSUNG TECHWIN. ALL RIGHT RESERVED.

SAMSUNG TECHWIN AMERICA INC. 100 Challenger Rd. Suite 700 Ridgefield Park, NJ 07660  
Toll Free : +1-877-213-1222 Direct : +1-201-325-6920 Fax : +1-201-373-0124

SAMSUNG TECHWIN EUROPE LTD. 2nd floor No5, The Height, Brookland, Weybridge, Surrey, U.K. KT13 0NY  
Tel : +44-1932-82-6700 Fax : +44-1932-82-6701

SHANGHAI SAMSUNG TECHWIN CO., LTD. 32F, Bk B, International Business Center, No. 391 Guiping Rd., Shanghai, China, 200233  
Tel : +86-21-5427-1155 Fax : +86-21-5423-5122

Design and specifications are subject to change without notice.



SAMSUNG TECHWIN

Security Solutions

Product Line-up  
2014 3rd Quarter



SAMSUNG TECHWIN

SAMSUNG

FIRST EDITION 07-2014



# NETWORK

## Network Camera

Wise/Vet.III

### Box

#### SNB-7004



##### 3MP Full HD Box Camera

- Max. 3M (2,048x1,536) resolution
- 30fps@2,048 x 1,536 / 60fps@1,920 x 1,080
- Simple focus, P-Iris, WDR (120dB)
- Day & Night (ICR), Enhanced DIS, Defog
- micro SD/SDHC/SDXC memory slot
- Built-in mic.

#### SNB-7001



##### 3MP Full HD Box Camera

- Max. 3M (2,048x1,536) resolution
- H.264, MJPEG dual codec
- Multiple streaming
- Smart compression (ROI encoding)
- Tampering, PoE

#### SNB-6010



##### 2MP 4.6mm Remote Head Camera

- Max. 2M (1,920x1,080) resolution
- 30fps@1,920 x 1,080
- WDR (120dB)
- Advanced motion detection, Defog, VA
- Multi-crop streaming
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming

#### SNB-6004/6003



##### 2MP Full HD Box Camera

- Max. 2M (1,920x1,080) resolution
- 60fps@1,920 x 1,080
- Enhanced DIS, Defog
- Simple focus (SNB-6004), P-Iris
- WDR (120dB)
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming

#### SNB-5004/5003



##### 1.3MP HD Box Camera

- Max. 1.3M (1,280x1,024) resolution
- 60fps @ 1,280x1,024
- Simple focus, Day & Night (ICR) (SNB-5004)
- WDR (130dB), Enhanced DIS, Defog
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming

#### SNB-5001



##### 1.3MP HD Box Camera

- Max. 1.3M (1,280x1,024) resolution
- H.264, MJPEG dual codec
- Multiple streaming
- Tampering, PoE

#### SNB-3002



##### 4CIF WDR Box Camera

- Max. 30(25)fps at 4CIF resolution
- H.264, MPEG-4, MJPEG multiple codec
- Multiple streaming, Tampering
- Tampering, MD
- PoE, SD memory, Bi-directional audio

#### SNZ-5200



##### 1.3MP HD 20x Zoom Camera

- Max. 1.3M (1,280x1,024) resolution
- 20x zoom (4.45 ~ 89mm)
- H.264, MPEG-4, MJPEG multiple codec
- Multiple streaming
- PoE, SD memory, Bi-directional audio

#### SNO-7084R



##### 3MP Full HD Weatherproof IR Camera

- Max. 3M(2,048x1,536) resolution
- 30fps@2,048 x 1,536 / 60fps@1,920 x 1,080
- 3 ~ 8.5mm (2.8x) Motorized V/F lens
- Simple focus (Motorized VF), P-Iris, WDR (120dB)
- Day&Night (ICR), Enhanced DIS, Defog
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming, IP66, IK10

#### SNO-6084R/6011R



##### 2MP Full HD Weatherproof IR Camera

- Max. 2M (1,920 x 1,080) resolution
- 60fps@1,920 x 1,080 (SNO-6084R)
- 30fps@1,920 x 1,080 (SNO-6011R)
- 3 ~ 8.5mm (2.8x) Motorized V/F lens (SNO-6084R)
- 3.8mm fixed lens (SNO-6011R)
- Day & Night (ICR), WDR (120dB)
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming, IP66 • IK10 (SNO-6084R)

## Dome

Wise/Vet.III

#### SNF-8010/8010VM



1P66 1K10 8010VM

##### 5MP 360 Degree Fisheye Camera

- Max. 5M(2,560x2,048) resolution
- 20fps@2,560x2,048
- Various viewing composition, 6 dewarping view mode
- Digital PTZ, Bi-directional audio
- MD, AD, Heat map, People counting
- micro SD/SDHC/SDXC memory slot
- IP66, IK10, EN50155, EN61373, M12 (SNF-8010VM)

#### SNF-7010/7010V/7010VM



1P66 1K10 7010V/7010VM

##### 3MP 360 Degree Fisheye Camera

- Max. 3M(2,048x1,536) resolution
- 20fps@2,048 x 1,536 • WDR (120dB)
- Various viewing composition
- Digital PTZ, Bi-directional audio
- micro SD/SDHC/SDXC memory slot
- IP66, IK10 and EN50155 (SNF-7010V/7010VM)
- M12 (SNF-7010VM)

#### SND-7084



##### 3MP Full HD Dome Camera

- Max. 3M(2,048x1,536) resolution
- 30fps @ 2,048 x 1,536 / 60fps @ 1,920 x 1,080
- 3 ~ 8.5mm (2.8x) Motorized V/F lens
- Simple focus (Motorized VF), P-Iris, WDR (120dB)
- Day&Night (ICR), Enhanced DIS, Defog
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming, Built-in mic.

#### SND-7061



##### 3MP Full HD Dome Camera

- Max. 3M (2,048x1,536) resolution
- 2.8x V/F lens (3 ~ 8.5mm)
- H.264, MJPEG dual codec
- Smart compression (ROI encoding)
- Multiple streaming, PoE

#### SND-6084/6083



##### 2MP Full HD Dome Camera

- Max. 2M(1,920x1,080) resolution
- 60fps @ 1,920 x 1,080
- 3 ~ 8.5mm (2.8x) V/F lens (Motorized : SND-6084)
- Simple focus (SND-6084)
- Day & Night (ICR : SND-6084)
- WDR (120dB), DIS, Defog
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming

## IR Dome

Wise/Vet.III

#### SND-5084/5083



##### 1.3MP HD Dome Camera

- Max. 1.3M (1,280 x 1,024) resolution
- 60fps@1,280 x 1,024
- 3 ~ 8.5mm (2.8x) motorized V/F lens (SND-5084)
- 2.8 ~ 10mm (3.6x) V/F lens (SND-5083)
- Day & Night (ICR), Enhanced DIS, Defog
- WDR (130dB)
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming

#### SND-5061/5011



##### 1.3MP HD Dome Camera

- Max. 1.3M (1,280x1,024) resolution
- 2.8x V/F lens (3 ~ 8.5mm) (SND-5061)
- 3mm fixed lens (SND-5011)
- H.264, MJPEG dual codec
- Multiple streaming, PoE

#### SND-3082



##### 4CIF WDR Dome Camera

- Max. 30(25)fps at 4CIF resolution
- 3.9x V/F lens (2.8 ~ 11mm)
- H.264, MPEG-4, MJPEG multiple codec
- Multiple streaming
- Tampering, MD
- PoE, Bi-directional audio

#### SND-7084R



##### 3MP Full HD IR Dome Camera

- Max. 3M(2,048x1,536) resolution
- 30fps @ 2,048 x 1,536 / 60fps @ 1,920 x 1,080
- 2.8x Motorized V/F Lens (3 ~ 8.5mm)
- Simple focus (Motorized V/F), P-Iris, WDR (120dB)
- Day&Night (ICR), Enhanced DIS, Defog
- micro SD/SDHC/SDXC memory slot
- Bi-directional audio support
- Multi-crop streaming, IR LED

#### SND-6084R



##### 2MP Full HD IR Dome Camera

- Max. 2M(1,920x1,080) resolution
- 60fps @ 1,920 x 1,080
- 3 ~ 8.5mm (2.8x) motorized V/F lens
- Simple focus, WDR (120dB)
- Day&Night (ICR), Enhanced DIS, Defog
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming, IR LED

## Vandal-Resistant

Wise/Vet.III

#### SND-6011R



##### 2MP Full HD IR Dome Camera

- Max. 2M(1,920x1,080) resolution
- 30fps @ 1,920 X 1,080
- 3.8mm fixed lens
- Day&Night (ICR), Enhanced DIS, Defog
- WDR (120dB)
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming, IR LED

#### SND-5084R



##### 1.3MP HD IR Dome Camera

- Max. 1.3M (1,280x1,024) resolution
- 60fps@1,280 X 1,024
- 3 ~ 8.5mm (2.8x) motorized V/F lens
- Simple focus, P-Iris, WDR (130dB)
- Day & Night (ICR), Enhanced DIS, Defog
- micro SD/SDHC/SDXC memory slot
- Built-in mic. • Multi-crop streaming, IR LED

#### SNV-7084



1P66 1K10

##### 3MP Full HD Vandal-Resistant Dome Camera

- Max. 3M(2,048x1,536) resolution
- 30fps@2,048x1,536 / 60fps@1,920x1,080
- 2.8x Motorized V/F lens (3 ~ 8.5mm)
- Simple focus(Motorized VF), P-Iris
- Day&Night (ICR), Enhanced DIS, Defog
- WDR (120dB) • micro SD/SDHC/SDXC memory slot
- Multi-crop streaming • IP66, IK10

#### SNV-6084



1P66 1K10

##### 2MP Full HD Vandal-Resistant Dome Camera

- Max. 2M (1,920 x 1,080) resolution
- 60fps@1,920 x 1,080
- 2.8x Motorized V/F lens (3 ~ 8.5mm)
- Simple focus (ICR), Enhanced DIS, Defog
- WDR (120dB), Simple focus
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming • PoE, IP66, IK10

#### SNV-6013



1P66 1K10

##### 2MP Full HD Vandal-Resistant Compact Dome Camera

- Max. 2M(1,920x1,080) resolution
- 60fps @ 1,920 x 1,080
- 2.8mm fixed lens
- WDR (120dB)
- MD, AD, FD, Video analytics
- IP66, IK10

#### SNV-6012M



1P66 1K10

##### 2MP Full HD Vandal-Resistant Mobile Flat Camera

- Max 2M (1,920 x 1,080) resolution
- 60fps @ 1,920 x 1,080
- 3mm fixed lens
- Day & Night (Electrical), Enhanced DIS, Defog
- WDR (120dB), micro SD/SDHC/SDXC memory slot
- IP66, IK10, M12, EN50155, EN50121
- PoE

#### SNV-5084



1P66 1K10

##### 1.3MP HD Vandal-Resistant Dome Camera

- Max. 1.3M (1,280x1,024) resolution
- 60fps @ 1,280x1,024
- 3 ~ 8.5mm (2.8x) Motorized V/F lens
- Simple focus, Day & Night (ICR)
- WDR (130dB), Enhanced DIS, Defog
- micro SD/SDHC/SDXC memory slot
- PoE, IP66, IK10

#### SNV-3082



1P66 1K10

##### 4CIF WDR Vandal-Resistant Dome Camera

- Max. 30(25)fps at 4CIF resolution
- 3.9x V/F lens (2.8 ~ 11mm)
- H.264, MPEG-4, MJPEG multiple codec
- PoE, SD memory, Bi-directional audio
- Multiple streaming, IP66, IK10

#### SNV-7084R



1P66 1K10

##### 3MP Full HD Vandal-Resistant IR Dome Camera

- Max. 3M(2,048x1,536) resolution
- 30fps@2,048x1,536 / 60fps@1,920x1,080
- Simple focus(Motorized VF), P-Iris, WDR (120dB)
- Day&Night (ICR), Enhanced DIS, Defog
- micro SD/SDHC/SDXC memory slot
- Multi-crop streaming
- IP66, IK10, IR LED

#### SNV-6084R



1P66 1K10

##### 2MP Full HD Vandal-Resistant IR Dome Camera

- Max. 2M (1,920x1,080) resolution
- 60fps @ 1,920 X 1,080
- 3 ~ 8.5mm (2.8x) motorized V/F lens
- Simple focus, Day&Night (ICR), Defog, WDR (120dB)
- H.264/MJPEG dual codec, Multiple streaming
- Multi-crop streaming
- PoE, Bi-directional audio • IP66, IK10, IR LED

#### SNV-5084R



1P66 1K10

##### 1.3MP HD Vandal-Resistant IR Dome Camera

- Max. 1.3M (1,280x1,024) resolution
- 60fps@1,920 x 1,080
- 3 ~ 8.5mm (2.8x) motorized V/F lens
- Simple focus, P-Iris
- Day & Night (ICR), Enhanced DIS, Defog
- WDR (130dB) • micro SD/SDHC/SDXC memory slot
- Multi-crop streaming, IP66, IK10, IR LED

#### PTZ Dome

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new

Wise/Vet.III new



# NETWORK / ANALOG

## Management Software

### SSM-VM10/20



#### Video Wall Monitor Management Software

- SSM-VM10 : Up to 16monitors display control
- SSM-VM20 : Up to 36monitors display control
- Run on standard PCs and displays
- Live monitoring / Sequence mode
- Event-driven virtual salvo switching
- Easy set & control through VM manager, SSM console

### SSM mobile



#### SSM Mobile viewer for Android / iOS

- Local / remote connection to SSM
- View layout / device list by user
- View live streaming video with PTZ control
- Supported format : H.264/MJPEG
- Calendar search / playback / bookmark functions

### SmartViewer



#### Easy Central Management Software

- Up to 36 videos monitoring from the connected devices
- Support for full screen mode
- Support for sequence function
- Favorite view & sequence of favorites
- Up to 16 videos simultaneous playback

### iPOLiS mobile



#### Mobile viewer for Android / iOS

- View live streaming video with PTZ control from the connected devices
- Supported format : H.264/MJPEG
- Video image flip / mirror, Video image capture
- Calendar search / playback / bookmark functions for DVRs / NVRs

### SPC-2000



#### Controller

- Superior system compatibility
- 3D joystick control
- Quick and easy installation
- SSM support

## Analog Camera

BEYOND

### Box

### SCB-5005/5003/5000



#### 1000TVL High Resolution Box Camera

- 1000TVL
- 0.03Lux@F1.2(Color), 0.003Lux(B/W) (SCB-5005, 5003)
- Day & Night (ICR : SCB-5005, 5003)
- WDR (120dB : SCB-5005, 5003)
- Simple focus, P-Iris (SCB-5005, 5003)
- SSDR, SSNR IV, Defog
- Intelligent video (SCB-5005, 5003)
- Coaxial control

### SCB-4000



#### High Resolution Box Camera

- 600TVL (Color), 700TVL (B/W)
- 0.1Lux@F1.2 (Color), 0.01Lux (B/W)
- Day & Night (ICR), Intelligent video
- Coaxial control, RS-485

### SCB-3003/3001/3000



#### Premium Resolution WDR Camera

- 700TVL (Color : SCB-3003), 650TVL (Color : SCB-3001), 600TVL (Color : SCB-3000)
- 0.1Lux@F1.2 (Color), 0.01 Lux (B/W) (SCB-3003/3001)
- 0.3Lux@F1.2 (Color), 0.01 Lux (B/W) (SCB-3000)
- Day & Night (ICR)
- SSNR III, Coaxial Control, RS-485

### SCB-2005/2004



#### High Resolution Box Camera

- 700TVL (ER mode)
- 0.1Lux @F1.2
- MD, Defog
- Day & Night (ICR : SCB-2005)
- Coaxial Control

### SCB-2001



#### High Resolution Box Camera

- 600TVL (Color), 700TVL (B/W)
- 0.05Lux@F1.2 (Color), 0.01Lux (B/W)
- Day & Night (ICR), Intelligent video
- Coaxial control, RS-485

### SCB-2000/1001



#### High Resolution Box Camera

- 600TVL
- 0.05Lux@F1.2 (Color) (SCB-2000)
- 0.1Lux@F1.2 (Color) (SCB-1001)
- Day & Night (Electrical)
- MD, SSNR III (SCB-2000)
- SSNR, Defog (SCB-1001)
- Coaxial control

### SCB-3020



#### High Resolution ATM Camera

- 600TVL
- 0.45Lux@F2.0 (Color)
- Fixed lens (3.7mm)
- WDR, VPS, Intelligent video
- Coaxial control

### SCZ-3430



#### High Resolution 43x WDR Zoom Camera

- 600TVL (Color), 700TVL (B/W)
- 0.7Lux@F1.65 (Color), 0.07Lux (B/W)
- 43x zoom (3.2 ~ 138.5mm), digital 16x
- WDR, VPS, Day & Night (ICR), Intelligent video
- Coaxial control

### SCZ-3370/2370



#### High Resolution 37x Zoom Camera

- 600TVL (Color), 700TVL (B/W) (SCZ-3370)
- 600TVL (Color), 680TVL (B/W) (SCZ-2370)
- 0.7Lux@F1.6 (Color), 0.07Lux (B/W) (SCZ-3370)
- 0.2Lux@F1.6 (Color), 0.02Lux (B/W) (SCZ-2370)
- 37x zoom (3.5 ~ 129.5mm), digital 16x
- Day & Night (ICR), SSNR III
- WDR, VPS, Intelligent video (SCZ-3370)

### SCZ-2373/2273



#### High Resolution 37x/27x Zoom Camera

- 680TVL (ER mode)
- 0.2Lux@F1.6 (Color), 0.01Lux (B/W)
- 37x zoom (3.5 ~ 129.5mm), Digital 16x (SCZ-2373)
- 27x zoom (3.5 ~ 94.5mm), Digital 16x (SCZ-2273)
- Day & Night (ICR), SSNR III, MD

### Zoom Box

### SCZ-2250



#### High Resolution 25x Zoom Camera

- 600TVL (Color), 700TVL (B/W)
- 0.2Lux@F1.65 (Color), 0.02Lux (B/W)
- 25x zoom (3.6 ~ 91.36mm), digital 16x
- Day & Night (ICR), Intelligent video
- Coaxial control

### SCO-5083R



1P66 1K10

#### High Resolution WDR Weatherproof IR Camera

- 1000TVL
- 0Lux (IR LED On), IR distance 50m
- 3.3x V/F Lens (3 ~ 10mm)
- WDR (120dB), Day & Night (ICR)
- SSDR, SSNR IV, Defog
- Intelligent video
- IP66, IK10, Coaxial control

### SCO-2081R



1P66

#### Premium Resolution Weatherproof IR Camera

- 700TVL (color)
- 0Lux (IR LED On), IR distance 50m
- 3.6x Varifocal lens (2.8 ~ 10mm)
- Day & Night (ICR), MD, SSNR III, Defog
- Coaxial control, RS-485, Dual power
- IP66

### SCO-2040R/2030R



1P66

#### High Resolution Small IR One Body Camera

- 650TVL
- 0Lux (IR LED on), IR distance 25m
- Fixed lens (8mm : SCO-2040R) (6mm : SCO-2040R)
- Coaxial control, RS-485, Dual power
- DNR, 12V DC, IP66

### SCO-2120R



1P66

#### High Resolution 12x Weatherproof IR Camera

- 600TVL (Color), 700TVL (B/W)
- 0Lux (IR LED On), IR distance 70m
- 12x zoom (3.94 ~ 46.05mm), digital 16x
- Day & Night (ICR), SSNR III
- IP66, Coaxial control

### Bullet

BEYOND

### SCO-2080R



1P66

#### High Resolution Weatherproof IR Camera

- 600TVL (Color), 700TVL (B/W)
- 0Lux (IR LED On), IR distance 50m
- 3.6x V/F lens (2.8 ~ 10mm)
- Day & Night (ICR), SSNR III
- IP66, Coaxial control

### SCO-1020R



1P66

#### Small Weatherproof IR Camera

- 520TVL
- 0Lux (IR LED On), IR distance 15m
- Fixed lens (3.6mm)
- IP66

### SCD-5083/5080



#### High Resolution 1000TVL Dome Camera

- 1000TVL
- 0.03Lux@F1.2 (Color), 0.003Lux (B/W) (SCD-5083)
- 0.05Lux@F1.4 (SCD-5080)
- Day & Night (ICR : SCD-5083)
- WDR (120dB : SCD-5083)
- 3.8x V/F Lens (2.8 ~ 10.5mm) (SCD-5083)
- 3.3x V/F Lens (3 ~ 10mm) (SCD-5080)
- SSDR, SSNR IV, Defog
- Intelligent video (SCD-5083)
- Coaxial control

### SCD-5030/5020



#### Premium Resolution 1000TVL Dome Camera

- 1000TVL
- 0.09Lux@F1.8
- Day & Night (Electrical)
- Fixed lens (3.6mm : SCD-5020)
- Fixed lens (6.0mm : SCD-5030)
- SSDR, SSNR IV, Defog
- Coaxial control, DV 12V

### SCD-3083/3080



#### High Resolution WDR Dome Camera

- 700TVL (Color : SCD-3083), 600TVL (Color : SCD-3080), 700TVL (B/W)
- 0.1Lux@F1.2 (Color), 0.01 Lux (B/W) (SCD-3083)
- 0.3Lux@F1.2 (Color), 0.01 Lux (B/W) (SCD-3080)
- 2.8x motorized V/F Lens (3 ~ 8.5mm) (SCD-3083), 3.9x V/F Lens (2.8 ~ 11mm) (SCD-3080)
- WDR, VPS, Day & Night (ICR), Intelligent Video
- Coaxial Control

# ANALOG

## Analog Camera

### SCD-2080/2080E/2060E



#### High Resolution Varifocal Dome Camera

- 600TVL (Color), 700TVL (B/W)
- 0.15Lux@F1.2 (Color), 0.01Lux (B/W) (SCD-2080)
- 0.15Lux@F1.2 (Color), 0.01Lux@F1.2 (Color), 0.01Lux (B/W) (SCD-2080E/2060E)
- 3.6x V/F lens (2.8 ~ 10mm) (SCD-2080/2080E)
- 2.4x V/F lens (2.5 ~ 6mm) (SCD-2060E)
- Day & Night (ICR : SCD-2080), SSNR III, Coaxial control

### Dome

### SCD-2082



#### Premium Resolution Varifocal Dome Camera

- 700TVL (Color)
- 0.1Lux@F1.2 (Color)
- 3.6x V/F lens (2.8 ~ 10mm)
- MD, SSNR III, Defog, Coaxial control
- Day & Night (Electrical)

### SCD-2022



#### Premium Resolution Small Dome Camera

- 700TVL (Color)
- 0.1Lux@F1.2 (Color)
- Fixed lens (3.8mm)
- MD, SSNR III, Defog, Coaxial control
- Day & Night (Electrical)

### SCD-2020/2010



#### High Resolution Small Dome Camera

- 600TVL
- 0.15Lux@F1.2 (Color) (SCD-2020)
- 0.04Lux@F1.2 (Color) (SCD-2010)
- Fixed lens (3.7mm) (SCD-2020)
- Fixed lens (3mm) (SCD-2010)
- SSNR III, Coaxial control

### SCD-2010F



#### High Resolution Compact Flat Camera

- 600TVL
- 0.04Lux@F1.2 (Color)
- Fixed lens (3mm)
- Coaxial control, 12V DC

### IR Dome

BEYOND

### SCD-1080/1020



#### High Resolution Varifocal Dome Camera

- 600TVL
- 0.15Lux@F1.2 (Color)
- 3.6x V/F lens (2.8 ~ 10mm) (SCD-1080)
- Fixed lens (3.6mm) (SCD-1020)
- Day & Night (Electrical), Coaxial control

### SCD-5083R



#### High Resolution 1000TVL WDR IR Dome Camera

- 1000TVL
- 0.05Lux@F1.4 (Color), 0Lux (IR LED on), IR Distance 20m
- Day & Night (ICR), WDR (120dB)
- 3.3x V/F Lens (3 ~ 10mm)
- SSDR, SSNR IV, Defog
- Intelligent video
- Coaxial control

### SCD-2080R/2021R



#### High Resolution Small IR Dome Camera

- 600TVL (Color), 700TVL (B/W) (SCD-2080R)
- 650TVL (Color) (SCD-2021R)
- 0Lux (IR LED on), IR distance 20m
- 3.6x V/F Lens (2.8 ~ 10mm) (SCD-2080R), Fixed lens (3.6mm) (SCD-2021R)
- 12V DC

### SCD-2042R/2022R



#### Premium Resolution IR Dome Camera

- 700TVL
- 0Lux (IR LED on), IR distance 7m
- Fixed lens 8mm (SCD-2042R)
- 3.8mm (SCD-2022R)
- Day & Night (ICR), SSNR III, Defog
- Coaxial control, 12V DC

### SCD-2020R/1020R



#### High Resolution Small IR Dome Camera

- 600TVL (Color), 700TVL (B/W), 0Lux (IR LED on), IR distance 7m (SCD-2020R)
- 520TVL (Color), 0Lux (IR LED on), IR distance 10m (SCD-1020R)
- Fixed lens (3.6mm)
- Day & Night (ICR), MD, SSNR III (SCD-2020R)

### Vandal-Resistant

BEYOND

### SCV-5083



1P66 1K10

#### High Resolution 1000TVL WDR Vandal Resistance Dome Camera

- 1000TVL
- 0.03Lux@F1.2 (Color), 0.003Lux (B/W)
- Day & Night (ICR), WDR (120dB)
- 3.8x V/F Lens (2.8 ~ 10.5mm)
- SSDR, SSNR IV, Defog
- Intelligent video
- Coaxial control, IP66, IK10

### SCV-3083/3082



1P66 1K10

#### High Resolution WDR Vandal Resistance Dome Camera

- 700TVL (Color : SCV-3083), 650TVL (Color : SCV-3082), 700TVL (B/W)
- 0.1Lux@F1.2 (Color), 0.01 Lux (B/W)
- 2.8x motorized V/F lens (3 ~ 8.5mm) (SCV-3083)
- 3.6x V/F lens (2.8 ~ 10mm) (SCV-3080)
- WDR, VPS, Day & Night (ICR), Intelligent Video
- IP66, Coaxial Control
- IK10 (SCV-3082)

### SCV-3080/2080



1P66 1K10

#### High Resolution Vandal-Resistant Dome Camera

- 600TVL (Color), 700TVL (B/W)
- 0.3Lux@F1.2 (Color), 0.01Lux (B/W) (SCV-3080)
- 0.15Lux@F1.2 (Color), 0.001Lux (B/W) (SCV-2080)
- 3.9x V/F Lens (2.8 ~ 11mm) (SCV-3080)
- 3.6x V/F lens (2.8 ~ 10mm) (SCV-2080)
- WDR, VPS, Intelligent video (SCV-3080)
- IP66, IK10, Coaxial control, Day & Night (ICR)

### IR Vandal-Resistant

BEYOND

### SCV-5083R



1P66 1K10

#### High Resolution 1000TVL WDR Vandal Resistance IR Dome Camera

-



ANALOG / DVR

Analog Camera		IR PTZ Dome	Positioning	HD-SDI	
SCP-2120		SCP-2370RH	SCU-2370	SCD-6021	SCB-6001/SCO-6081R
					
High Resolution 12x PTZ Dome Camera		High Resolution 37x IR PTZ Dome Camera	High Resolution 37x Weatherproof Positioning System	1080P HD-SDI WDR Dome Camera	1080P HD-SDI Box / Weatherproof WDR IR Camera
• 600TVL (Color), 700TVL (B/W) • 0.2Lux@F1.67 (Color), 0.004Lux (B/W) • 12x zoom (3.9 ~ 46mm) • Day & Night (ICR), SSNRIII, Coaxial control		• 600TVL (Color), 700TVL (B/W) • 0Lux (IR LED on), IR distance 100m • 37x zoom (3.5 ~ 129.5mm) • Day & Night (ICR), SSNRIII • IP66, IK10, Coaxial control	• 600TVL (Color), 700TVL (B/W) • 0.2Lux@F1.6 (Color), 0.02Lux (B/W) • 37x zoom (3.5 ~ 129.5mm) • Day & Night (ICR), SSNRIII • IP66, Coaxial control	• Full HD (1,920 × 1,080, 30fps), HD (1,280 × 720, 60fps) • 0.5Lux@F2.0(Color) / Fixed lens (3.8mm) • Day & Night (Electrical), WDR (100dB), MD • SSNRIII, 12V DC	• Full HD (1,920 × 1,080, 30fps), HD (1,280 × 720, 60fps) • 1Lux@F1.2 (Color), 0.1Lux (B/W) (SCB-6001) • 0Lux (IR LED on), IR distance 30m (SCO-6081R) • 2.8x motorized V/F lens (3~8.5mm) (SCO-6081R) • Day & Night (ICR), WDR(100dB), RS-485 • IP66 (SCO-6081R)
UTP					Thermal
SCD-6081R/SCV-6081R		SUB-2000	SUD-3080	SUD-2081/2080	SCB-9080/9060
					
1080P HD-SDI WDR IR Dome / Vandal-Resistant Dome Camera		High Resolution UTP Camera	High Resolution WDR UTP Dome Camera	High Resolution UTP Dome Camera	Weatherproof Thermal Camera
• Full HD (1,920 x 1,080, 30fps), HD (1,280 x 720, 60fps) • 0Lux (IR LED on), IR distance 15m • 2.8x motorized V/F lens (3~8.5mm) • Day & Night (ICR), MD, WDR (100dB), SSNRIII • IP66 (SCV-6081R)		• 600TVL • 0.05Lux@F1.2 (Color) • SSNRIII, Day & Night (Electrical) • Built-in UTP T/X • Coaxial control	• 600TVL (Color), 700TVL (B/W) • 0.3Lux@F1.2 (Color), 0.01Lux (B/W) • 3.9x V/F lens (2.8 ~ 11mm) • WDR, VPS, Day & Night (ICR), Intelligent video • Built-in UTP TX, Coaxial control	• 600TVL (Color), 700TVL (B/W) • 0.15Lux@F1.2 (Color), 0.001Lux (B/W) • 3.6x V/F lens (2.8 ~ 10mm) • Day & Night (ICR), MD, SSNRIII • Built-in UTP TX, Coaxial control	• Outstanding detection without lighting 1.2km (SCB-9080), 360m (SCB-9060) • Built-in 50mm, 0.47mrad (SCB-9080), Built-in 14mm, 1.68mrad (SCB-9060) • Min. discernable temperature of 0.08°C • Event alarm, Multi-language OSD, IP66
DVR		16CH			
SRD-1680D		SRD-1676D	SRD-1673D	SRD-1670D/1670DC	SRD-1656D
					
8/16CH HD-SDI Hybrid Recorder		16CH 1280H Real-time Coaxial DVR	16CH 960H Real-time Coaxial DVR	16CH 4CIF Real-time /Coaxial DVR	16CH CIF (1280H available) Real-time Coaxial DVR
• Real-time, 8CH@2M / 16CH@WD1,4CIF • HDMI/VGA video output • Max. 4 internal HDDs • HDD removable (Easy install) • Smart searching, Tampering support • PTZ Control via Coaxial Cable • Smart phone support, DVR-RW • Enhanced Network Bandwidth up to 64Mbps		• Up to 480(NTSC) / 400(PAL) fps recording rate • HDMI/VGA video output • Max. 4 internal HDDs • PTZ control via coaxial cable • Smart phone support, DVD-RW • Enhanced Network Bandwidth up to 32Mbps • MD, Tampering	• Up to 480(NTSC) / 400(PAL)fps recording rate • HDMI/VGA video output • Max. 4 internal HDD • PTZ control via coaxial cable • Smart phone support, DVD-RW • Enhanced Network Bandwidth up to 32Mbps	• Up to 480(NTSC) / 400(PAL)fps recording rate • HDMI/VGA video output • Max. 5 internal HDD • PTZ control via coaxial cable (SRD-1670DC) • Smart phone support, DVD-RW	• Up to 120(NTSC) / 100(PAL) fps recording rate • HDMI/VGA video output • Max. 4 internal HDDs • PTZ control via coaxial cable • Smart phone support, DVD-RW • Enhanced Network Bandwidth up to 32Mbps • MD, Tampering

SRD-1654D	SRD-1653D	SRD-1650D/1650DC	SRD-1652D	SRD-1642
				
16CH CIF Real-time DVR	16CH CIF (960H available) Real-time Coaxial DVR	16CH CIF Real-time / Coaxial DVR	16CH CIF Real-time DVR	16CH 960H Real-time Compact DVR
• 16CH, Real-time@CIF • Max. resolution of 960 x 480 / 960 x 576 • HDMI/VGA video output • Max. 4 internal HDDs • Smart searching • Smart phone support, DVD-RW • Enhanced Network Bandwidth up to 32Mbps	• Up to 480(NTSC) / 400(PAL)fps recording rate • HDMI/VGA video output • Max. 4 internal HDD • PTZ control via coaxial cable • Smart phone support, DVD-RW • Enhanced Network Bandwidth up to 32Mbps	• Up to 480(NTSC) / 400(PAL)fps recording rate • HDMI/VGA video output • Max. 5 internal HDD • PTZ control via coaxial cable (SRD-1650DC) • Smart phone support, DVD-RW	• Up to 480(NTSC) / 400(PAL)fps recording rate • VGA/Composite video output • Max. 4 internal HDD • Smart phone support, DVD-RW	• Up to 480(N) / 400(P) fps recording rate • HDMI/VGA video output • Max. 2 internal HDDs • PTZ control via coaxial cable • Smart phone support • Enhanced Network Bandwidth up to 32Mbps

SRD-880D	SRD-876D	SRD-873D	SRD-870DC	SRD-854D
				
8CH Full HD Real Time HD-SDI DVR	8CH 1280H Real-time Coaxial DVR	8CH 960H Real-time Coaxial DVR	8CH 4CIF Real-time Coaxial DVR	8CH CIF (960H available) Real-time DVR
• Real-time, 8CH@2M • HDMI/VGA video output • Max. 4 internal HDDs • HDD removable (Easy install) • Smart searching, Tampering support • Smart phone support, DVD-RW • Enhanced Network Bandwidth up to 64Mbps	• Up to 240(NTSC) / 200(PAL) fps recording rate • HDMI/VGA video output • Max. 4 internal HDDs • PTZ control via coaxial cable • Smart phone support, DVD-RW • Enhanced Network Bandwidth up to 32Mbps • MD, Tampering	• Up to 240(NTSC) / 200(PAL)fps recording rate • HDMI/VGA video output • Max. 4 internal HDD • PTZ control via coaxial cable • Smart phone support, DVD-RW • Enhanced Network Bandwidth up to 32Mbps	• Up to 240(NTSC) / 200(PAL)fps recording rate • HDMI/VGA video output • Max. 5 internal HDD • PTZ control via coaxial cable • Smart phone support, DVD-RW	• 8CH, Real-time@CIF • Max. resolution of 960 x 480 / 960 x 576 • HDMI/VGA video output • Max. 4 internal HDDs • Smart searching • Smart phone support, DVD-RW • Enhanced Network Bandwidth up to 32Mbps

DVR / Lens / Peripheral / Monitor

DVR	8CH	4CH		
SRD-850D/850DC	SRD-852D	SRD-842	SRD-482	SRD-476D
				
8CH CIF Real-time / Coaxial DVR	8CH CIF Real-time DVR	8CH 960H Real-time Coaxial DVR	4CH Full HD Real Time HD-SDI DVR	4CH 1280H Real-time Coaxial DVR
• Up to 240(NTSC) / 200(PAL)fps recording rate • HDMI/VGA video output • Max. 5 internal HDD • PTZ control via coaxial cable (SRD-850DC) • Smart phone support, DVD-RW	• Up to 240(NTSC) / 200(PAL)fps recording rate • VGA/Composite video output • Max. 4 internal HDD • Smart phone support, DVD-RW	• Up to 240(NTSC) / 200(PAL) fps recording rate • HDMI/VGA video output • Max. 2 internal HDDs • PTZ control via coaxial cable • Smart phone support • Enhanced Network Bandwidth up to 8Mbps	• Real-time, 4CH@2M • HDMI/VGA video output • Max. 2 internal HDDs • Smart searching, Tampering support • Smart phone support • Enhanced Network Bandwidth up to 64Mbps	• Up to 120(NTSC) / 100(PAL) fps recording rate • HDMI/VGA video output • Max. 1 internal HDDs • PTZ control via coaxial cable • Smart phone support, DVD-RW • Enhanced Network Bandwidth up to 16Mbps • MD, Tampering
			HDD	Lens
			SVS-5R/5E	SLA-12240/880
				
			RAID 5 Unit /HDD Extension Unit	1/2" C-mount Motorized 20x /10x Zoom Lens
			• 1U 19-inch rack case • Data transmission speed : up to 3.0Gbps (SATA II) • Available SATA HDD : up to 4 (4TB)	• 1.3 Megapixel resolution (SLA-12240) VGA resolution (SLA-880) • 50mm lens with micro bolometer sensor • Auto Iris : DC(SLA-12240) / Video(SLA-880) • 20x optical zoom (12 ~ 240mm / 0.47" ~ 9.45")/ 10x optical zoom (8 ~ 80mm / 0.31" ~ 3.15")
			Peripheral	PTZ Dome Housings
			SHP-3701H/3701F/SHD-3000F1	SBP-300WM/300WM1/300B
				
			PTZ Housings	Wall Mount/Base
			• SHP-3701H • For outdoor applications - Aluminum + Polycarbonate IP66, IK10 • SHP-3701F/SHD-3000F1 - For indoor applications, Polycarbonate	• Aluminum + SECC • Can be used with hanging mount and outdoor PTZ (SBP-300WM/300WM1) • Can be used with SBP-300WM/300WM1 (SBP-300B)
			Fixed Housings	
			SHB-4300H/4300H1 /4300H2/4200/4200H	STH-500/200
				
			Fixed Housing	Fixed Housing
			• SHB-4300H / 4300H1 / 4300H2 - Aluminum diecasting construction, Fully cable managed bracket - Built-in fan & heater - Support three cable glands, IP66 • SHB-4200 / 4200H - Support two cable glands - Built-in fan & heater (SHB-4200H)	• For fixed camera application • Wall/ceiling installations • Easy to install side open type
			IR Illuminator	UTP
			SPI-10A/30A SBU-550IM	SPU-100TR/400/400R
				
			IR Illuminator / Bracket	HD-SDI Repeater / Converter
			• SPI-10A/30A - Viewable length of 100m (328.1ft) : SPI-10A / 70m (229.66ft) : SPI-30A - Radiation angle of 10° : SPI-10A / 30° : SPI-30A - IP66 • SBU-550IM - Applicable with SPI-10A/30A	• SPH-120R - Repeat the HD-SDI signal from the HD CCTV cameras - Enable the extension for the transmission distance • SPH-110C - Accepts the HD-SDI signal from the HD CCTV cameras - Convert the signal for presentation on the HDMI input of the monitor
			Positioning System / Explosion Proof Positioning System	UTP System
			• SCU-VAC - Integrated receiver, pan/tilt, and housing - Position encoders provide 0.1° accuracy - 360° pan, +40° to -85° tilt range - Accepts most 24V AC 3rd party cameras • SCU-EVAC - Integrated Pan/Tilt, and Housing - 360° pan, +90° to -90° tilt range - Telemetry Receiver (SPX-E100), IP66	• 1CH UTP Transceiver (SPU-100TR) • 4CH UTP Power Supply Hub (SPU-400) • 4CH UTP Power Supply Receiver (SPU-400R)
			Fixed Mount	
			• SBU-500WM/220PM - Wall/Pedestal mount for positioning system - Aluminum material - Can be used with SCU-2370/9080, SCU-VAC • STB-400/4150V - Bracket for STH-500/200 (STB-400) - Bracket for box cameras (STB-4150V) - Steel material	